

Application No.: 10/008553

Docket No.: MWS-009

**AMENDMENTS TO THE CLAIMS**

1. (Original) In an electronic device interfaced with a display surface, a method, comprising the steps of:
- providing two electronic diagrams, said electronic diagrams having blocks representing components of a system;
  - determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;
  - determining differences between said electronic diagrams; and
  - programmatically merging differences copied from a selected one of said two electronic diagrams into the other of said electronic diagrams at a corresponding location in said other electronic diagram.
2. (Original) The method of claim 1 wherein said programmatically merging differences comprises the further step of:
- replacing data elements of said other electronic diagram with copied differences from said selected one of said two electronic diagrams.
3. (Original) The method of claim 2, comprising the further step of:
- cascading hierarchically the replacement of data elements wherein said data elements being replaced are arranged in a tree structure, said tree structure having parent data elements with child data elements attached thereto, said child data elements being replaced when said parent data element is replaced.
4. (Original) The method of claim 3 wherein only said child data elements are replaced.
5. (Currently Amended) ~~The method of claim 1, comprising the further steps of:~~  
In an electronic device interfaced with a display surface, a method, comprising the steps of:  
providing two electronic diagrams, said electronic diagrams having blocks representing components of a system;

Docket No.: MWS-009

Application No.: 10/008553

determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;

determining differences between said electronic diagrams; and  
programmatically merging differences copied from a selected one of said two electronic diagrams into the other of said electronic diagrams at a corresponding location in said other electronic diagram;

categorizing said differences between said two electronic diagrams as functional differences and graphical differences, said functional differences controlling the performance of a system represented by said electronic diagram, said graphical differences affecting the appearance of said electronic diagram displayed to a user;

copying all of said functional differences from said selected one of said two electronic diagrams;

copying less than all of said graphical differences from said selected one of said two electronic diagrams; and

inserting the copied functional differences and graphical differences into corresponding sections of said other electronic diagram, said copied functional and graphical differences being inserted in the corresponding section of said other electronic diagram.

6. (Original) The method of claim 5, comprising the further steps of:

cascading hierarchically the replacement of data elements in said other electronic diagram wherein said data elements being replaced are arranged in a tree structure, said tree structure having parent data elements with child data elements attached thereto, said child data elements in said other electronic diagram being replaced when said parent data element is replaced.

7. (Original) The method of claim 5, comprising the further steps of:

cascading hierarchically the replacement of data elements in said other electronic diagram, wherein said data elements being replaced are arranged in a tree structure, said tree structure having parent data elements with child data elements attached thereto, said child data elements of corresponding parent data elements in said two electronic diagrams being replaced without replacing the corresponding parent data element.

Docket No.: MWS-009

Application No.: 10/008553

8. (Original) The method of claim 1, comprising the further steps of:

highlighting the differences in said electronic diagrams for a user on a display surface of a display device, said display surface showing both of said diagrams; and  
updating said display surface following the performance of said merging operation, said updating showing the differences copied to said other electronic diagram.

9. (Currently Amended) ~~The method of claim 8, comprising the further steps of:~~

In an electronic device interfaced with a display surface, a method, comprising the steps of:

providing two electronic diagrams, said electronic diagrams having blocks representing components of a system;

determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;

determining differences between said electronic diagrams; and

programmatically merging differences copied from a selected one of said two electronic diagrams into the other of said electronic diagrams at a corresponding location in said other electronic diagram;

determining a distance on said display surface from an endpoint of a line to an updated connection point for a block in said electronic diagram, said updated connection point being the connection point of a line and a block following a merge operation;

comparing said distance to a pre-defined parameter, said pre-defined parameter being a distance value;

extending said displayed arrowed line to said updated connection point when said distance is less than said pre-defined parameter.

10. (Original) The method of claim 9, comprising the further step of:

replacing said line with a new line drawn to said updated connection point when said distance is at least as large as said pre-defined parameter.

11. (Original) The method of claim 1, comprising the further steps of:

presenting said differences in said electronic diagrams on a display surface of a display device, said display surface split to show both of said electronic diagrams;

Docket No.: MWS-009

Application No.: 10/008553

highlighting a difference item in said selected one of said two electronic diagrams;  
highlighting a difference item in said other electronic diagram that corresponds to the  
matching highlighted difference in said selected one of said two electronic diagrams; and  
replacing the highlighted difference item in said other electronic diagram with a copy of  
the highlighted difference item from said selected one of said two electronic diagrams.

12. (Original) The method of claim 11 comprising the further step of:

replacing a data element in a highlighted difference item in said other electronic diagram,  
said data element being a child data element in said other electronic diagram, said data element  
being part of a tree structure, said tree structure having parent data elements with child data  
elements attached thereto.

13. (Currently Amended) The method of claim 1, wherein said two electronic diagrams are at  
least one of block diagrams, state diagrams, signal diagrams, flow chart diagrams, sequence  
diagrams, UML diagrams, dataflow diagrams, circuit diagrams, ladder logic diagrams and  
Kinematic element diagrams.

14. (Original) The method of claim 1, wherein said electronic diagrams depict multiple domains

15. (Original) In an electronic device, a method, comprising the steps of:

providing two state diagrams of a system, said state diagrams having blocks joined with  
lines, each of said blocks representing states in a system, said lines representing transitions  
between said states, said transitions taking place upon the occurrence of a specified event;

determining corresponding features of said state diagrams that are present in both of said  
state diagrams;

determining differences between said state diagrams, said differences being recorded as a  
list of data elements; and

merging differences from a selected one of said state diagrams into the other of said state  
diagrams, said merging copying said differences from the selected one of said state diagrams and  
inserting said differences in said other state diagram.

Docker No.: MWS-009

Application No.: 10/008553

16. (Original) The method of claim 15 wherein said merging differences comprises the further steps of:

replacing data elements of said other state diagram with copied differences of data elements from said selected one of said state diagrams.

17. (Original) The method of claim 15, comprising the further steps of:

categorizing said corresponding features as functional features and graphical features, said functional features controlling the performance of the system represented by said state diagram, said graphical features affecting the appearance of said state diagram displayed to a user;

determining differences in said functional features and said graphical features of said state diagrams;

copying all of said differences in functional features from said selected one of said state diagrams;

copying less than all of said differences in graphical features from said selected one of said state diagrams; and

inserting the copied functional feature differences and graphical feature differences into corresponding sections of said other state diagram, said copied differences replacing data elements in the corresponding section of said other state diagram.

18. (Currently Amended) In a network that includes an electronic device, said electronic device interfaced with a display surface, a method, comprising the steps of:

retrieving over said network two electronic diagrams, said electronic diagrams having blocks joined with lines and including at least one semantic connection, said semantic

connection associating components in said electronic diagram without a direct connection in said diagram, each of said blocks including connection points where said lines join said blocks;

displaying said electronic diagrams to a user on said display surface;

determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;

determining differences between said electronic diagrams, said differences being recorded as a list of data elements; and

Application No.: 10/008553

Docket No.: MWS-009

merging differences from a selected one of said electronic diagrams into the other of said electronic diagrams, said merging copying said differences from the selected one of said electronic diagrams and inserting said differences in the other of said electronic diagrams.

19. (Original) The method of claim 18, comprising the further steps of:

categorizing said differences between said electronic diagrams as functional differences and graphical differences, said functional differences controlling the performance of the system represented by said electronic diagram, said graphical differences affecting the appearance of said block diagram displayed to a user;

copying all of said functional differences from selected one of said electronic diagrams; copying less than all of said graphical differences from said other electronic diagram; and inserting the copied functional differences and graphical differences into corresponding sections of said other electronic diagram, said copied graphical and functional differences replacing data elements in the corresponding section of said other electronic diagram.

20. (Original) In an electronic device interfaced with a display surface, a medium holding computer-executable instructions for a method, said method comprising the steps of:

providing two electronic diagrams, said electronic diagrams having blocks representing components of a system, said blocks connected by lines;

determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;

determining differences between said electronic diagrams; and

programmatically merging differences copied from a selected one of said two electronic diagrams into the other of said electronic diagrams at a corresponding location in said other electronic diagram.

21. (Original) The medium of claim 20 wherein the step of merging differences in said method comprises the further step of:

replacing data elements of said other electronic diagram with copied differences from said selected one of said two electronic diagrams.

22. (Original) The medium of claim 20 wherein said method comprises the further step of:

Application No.: 10/008553

Docket No.: MWS-009

categorizing said differences between said two electronic diagrams as functional differences and graphical differences, said functional differences controlling the performance of a system represented by said electronic diagram, said graphical differences affecting the appearance of said electronic diagram displayed to a user,

copying all of said functional differences from said selected one of said two electronic diagrams;

copying less than all of said graphical differences from said selected one of said two electronic diagrams; and

inserting the copied functional differences and graphical differences into corresponding sections of said other electronic diagram, said copied functional and graphical differences being inserted in the corresponding section of said other electronic diagram.

A. 23. (Original) The medium of claim 20 wherein said method comprises the additional steps of:  
determining differences in at least one additional electronic diagram; and  
merging said differences from at least one additional electronic diagram into said electronic diagrams.

24. (Currently Amended) The medium of claim 20 wherein said method comprises the additional steps of:  
determining differences in at least one additional electronic diagram; and  
merging said differences from at least one additional electronic diagram into a single electronic diagram, said single electronic diagram being stored in a configuration management system.

25. (New) In an electronic device interfaced with a display surface, a method, comprising the steps of:  
providing two electronic diagrams, said electronic diagrams having blocks representing components of a system and including at least one semantic connection, said semantic

Docket No.: MWS-009

Application No.: 10/008553

connection associating components in said electronic diagram without a direct connection in said diagram;

determining corresponding features of said electronic diagrams that are present in both of said electronic diagrams;

determining differences between said electronic diagrams; and

programmatically merging differences copied from a selected one of said two electronic diagrams into the other of said electronic diagrams at a corresponding location in said other electronic diagram.

26. (New) The method of claim 25 wherein said programmatically merging differences comprises the further step of:

replacing data elements of said other electronic diagram with copied differences from said selected one of said two electronic diagrams.

27. (New) The method of claim 26, comprising the further step of:

A. cascading hierarchically the replacement of data elements wherein said data elements being replaced are arranged in a tree structure, said tree structure having parent data elements with child data elements attached thereto, said child data elements being replaced when said parent data element is replaced.

28. (New) The method of claim 27 wherein only said child data elements are replaced.

29. (New) The method of claim 25, comprising the further steps of:

highlighting the differences in said electronic diagrams for a user on a display surface of a display device, said display surface showing both of said diagrams; and

updating said display surface following the performance of said merging operation, said updating showing the differences copied to said other electronic diagram.

30. (New) The method of claim 25, comprising the further steps of:

presenting said differences in said electronic diagrams on a display surface of a display device, said display surface split to show both of said electronic diagrams;



Docket No.: MWS-009

Application No.: 10/008553

highlighting a difference item in said selected one of said two electronic diagrams;  
highlighting a difference item in said other electronic diagram that corresponds to the  
matching highlighted difference in said selected one of said two electronic diagrams; and  
replacing the highlighted difference item in said other electronic diagram with a copy of  
the highlighted difference item from said selected one of said two electronic diagrams.

31. (New) The method of claim 30 comprising the further step of:

replacing a data element in a highlighted difference item in said other electronic diagram,  
said data element being a child data element in said other electronic diagram, said data element  
being part of a tree structure, said tree structure having parent data elements with child data  
elements attached thereto.

A1  
32. (New) The method of claim 25, wherein said two electronic diagrams are at least one of  
block diagrams, state diagrams, signal diagrams, flow chart diagrams, sequence diagrams, UML  
diagrams, dataflow diagrams, circuit diagrams, ladder logic diagrams and Kinematic element  
diagrams.

33. (New) The method of claim 25, wherein said electronic diagrams depict multiple domains.

34. (New) In an electronic device interfaced with a display surface, said electronic device  
including a medium holding executable steps for a method, said method comprising the steps of:  
providing two electronic diagrams, said electronic diagrams having blocks representing  
components of a system and including at least one semantic connection, said semantic  
connection associating components in said electronic diagram without a direct connection in said  
diagram;

determining corresponding features of said electronic diagrams that are present in both of  
said electronic diagrams;

determining differences between said electronic diagrams; and

programmatically merging differences copied from a selected one of said two electronic  
diagrams into the other of said electronic diagrams at a corresponding location in said other  
electronic diagram.

Docket No.: MWS-009

Application No.: 10/008553

35. (New) The medium of claim 34 wherein said programmatically merging differences comprises the further step of:

replacing data elements of said other electronic diagram with copied differences from said selected one of said two electronic diagrams.

36. (New) The medium of claim 35 wherein said method comprises the further step of:  
cascading hierarchically the replacement of data elements wherein said data elements being replaced are arranged in a tree structure, said tree structure having parent data elements with child data elements attached thereto, said child data elements being replaced when said parent data element is replaced.

37. (New) The medium of claim 36 wherein only said child data elements are replaced.

38. (New) The medium of claim 34 wherein said method comprises the further steps of:  
highlighting the differences in said electronic diagrams for a user on a display surface of a display device, said display surface showing both of said diagrams; and  
updating said display surface following the performance of said merging operation, said updating showing the differences copied to said other electronic diagram.

39. (New) The medium of claim 34 wherein said method comprises the further steps of:  
presenting said differences in said electronic diagrams on a display surface of a display device, said display surface split to show both of said electronic diagrams;  
highlighting a difference item in said selected one of said two electronic diagrams;  
highlighting a difference item in said other electronic diagram that corresponds to the matching highlighted difference in said selected one of said two electronic diagrams; and  
replacing the highlighted difference item in said other electronic diagram with a copy of the highlighted difference item from said selected one of said two electronic diagrams.

40. (New) The medium of claim 39 wherein said method comprises the further step of:  
replacing a data element in a highlighted difference item in said other electronic diagram, said data element being a child data element in said other electronic diagram, said data element

Docket No.: MWS-009

Application No.: 10/008553

being part of a tree structure, said tree structure having parent data elements with child data elements attached thereto.

41. (New) The medium of claim 34 wherein said two electronic diagrams are at least one of block diagrams, state diagrams, signal diagrams, flow chart diagrams, sequence diagrams, UML diagrams, dataflow diagrams, circuit diagrams, ladder logic diagrams and Kinematic element diagrams.

42. (New) The medium of claim 34 wherein said electronic diagrams depict multiple domains

---